




RAD Power Machinery Co., Ltd.



7009 ACE/P4A Bearing 2D drawings and 3D CAD models

SKF 7009 ACE/P4A angular contact ball bearings

Bearing No. 7009 ACE/P4A

Size	75x45x16 mm
Bore Diameter	75 mm
Outer Diameter	45 mm
Width	16 mm
d	45 mm
D	75 mm
B	16 mm
d ₁	55.7 mm
d ₂	53.6 mm
D ₁	64.25 mm
r _{1,2} - min.	1 mm
r _{3,4} - min.	0.6 mm
a	22.2 mm
d _a - min.	49.6 mm
d _b - min.	49.6 mm
D _a - max.	70.4 mm
D _b - max.	70.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
d _n	57.6 mm
Basic dynamic load rating - C	12.1 kN
Basic static load rating - C ₀	8.2 kN
Fatigue load limit - P _u	0.345 kN
Limiting speed for grease	24000 r/min



RAD Power Machinery Co., Ltd.

Lubrication	
Limiting speed for oil lubrication	37000 mm/min
Ball - D_w	7.144 mm
Ball - z	21
G_{ref}	3.4 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	110 N
Preload class B - G_B	330 N
Preload class C - G_C	660 N
Calculation factor - f	1.06
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.03
Calculation factor - f_{2C}	1.06
Calculation factor - f_{HC}	1
Preload class A	94 N/micron
Preload class B	140 N/micron
Preload class C	183 N/micron
d_1	55.7 mm
d_2	53.6 mm
D_1	64.25 mm
$r_{1,2}$ min.	1 mm



RAD Power Machinery Co., Ltd.

$r_{3,4}$ min.	0.6 mm
d_a min.	49.6 mm
d_b min.	49.6 mm
D_a max.	70.4 mm
D_b max.	70.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
d_n	57.6 mm
Basic dynamic load rating C	12.1 kN
Basic static load rating C_0	8.15 kN
Fatigue load limit P_u	0.345 kN
Attainable speed for grease lubrication	24000 r/min
Attainable speed for oil-air lubrication	37000 r/min
Ball diameter D_w	7.144 mm
Number of balls z	21
Reference grease quantity G_{ref}	3.4 cm ³
Preload class A G_A	110 N
Static axial stiffness, preload class A	94 N/ μ m
Preload class B G_B	330 N
Static axial stiffness, preload class B	140 N/ μ m
Preload class C G_C	660 N
Static axial stiffness, preload class C	183 N/ μ m
Calculation factor f	1.06
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.03
Calculation factor f_{2C}	1.06
Calculation factor f_{HC}	1



RAD Power Machinery Co., Ltd.

Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.24 kg